

# TOP LINE LED 90W

COD. TOL18015




## DATI TECNICI | TECHNICAL DATA

<b>Nome Name</b>	TOP LINE LED 90W
<b>Materiali Materials</b>	Corpo in lamiera d'acciaio Sheet steel body
<b>Finiture Finishing</b>	Bianco RAL 9016 Opaco e Nero White RAL 9016 Matt and Black
<b>Elettronica Electronics</b>	ON/OFF
<b>Rischio fotobiologico Photobiologic risk</b>	Classe 0 Class 0
<b>Grado di protezione IP rating</b>	IP54
<b>Alimentazione Power Supply</b>	220-240V 50/60Hz
<b>Sorgente luminosa Luminous source</b>	Modulo LED LED module
<b>Potenza Wattage</b>	90W
<b>Sistema ottico Optic system</b>	Schermo parabolico - vetro temperato Parabolic louvre - toughened glass
<b>Temperatura colore Colour temperature</b>	4000K
<b>Resa cromatica Colour rendering</b>	CRI > 80
<b>Peso Weight</b>	6,5kg
<b>Misura Size</b>	AxBxC 675x190x160mm
<b>Accessori Accessories</b>	Personalizzabile su richiesta Customized on request

## PARAMETRI FOTOMETRICI | PHOTOMETRIC PARAMETERS

<b>Efficacia luminosa Luminous efficiency</b>	103,14Lm/W
<b>Codice fotometria Photometric code</b>	LAB.PLU.001/15
<b>Flusso luminoso Lumen output</b>	9283,40Lm



## SCHERMO PARABOLICO LED PARABOLIC LOUVRE LED

Apparecchio a sorgente LED progettato per grandi aree logistiche interne. Adatto per l'installazione ad altezze elevate. Predisposto per l'aggancio a blindosbarra.

LED light source luminaire suitable for large internal and logistical areas. Designed to be installed at elevated heights and to be attached to metal-enclosed wiring ducts, too.

## DISEGNO TECNICO | TECHNICAL DRAWING

